



△
Notes:
When you fix the main body to the panel cut hole by fixed metal fittings,
please be careful not to apply excessive torque during tightening of the screw of fixed metal fittings.

Please tightening up of a fixed screw by the torque of the degree
which uses the #1 cross-head screwdriver and makes a driver revolve by a fingertip.
(Attention: The thickness of the shaft of the #1 cross-head screwdriver is around 10-20mm)

				TENSION METER	
				TM340-DC	
				Dimensional drawing	
REV.	DATE	REV-No	DESCRIPTION	REV	CKD
1	MAR.04'20	A29391	REV.	S.Tadachi	H.Narumi
2	FEB.22'16	A18083	REV.	H.Ando	T.Yonakura
3					
4					
5					
6					
7					
8					
9					
10					
11					
12					
13					
14					
15					
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					
26					
27					
28					
29					
30					
31					
32					
33					
34					
35					
36					
37					
38					
39					
40					
41					
42					
43					
44					
45					
46					
47					
48					
49					
50					
51					
52					
53					
54					
55					
56					
57					
58					
59					
60					
61					
62					
63					
64					
65					
66					
67					
68					
69					
70					
71					
72					
73					
74					
75					
76					
77					
78					
79					
80					
81					
82					
83					
84					
85					
86					
87					
88					
89					
90					
91					
92					
93					
94					
95					
96					
97					
98					
99					
100					

NIRECO
NIRECO CORPORATION