



TKM/9024VDC

- Metal enclosure
- High holding force

Data

Ordering data

| | |
|-------------------------------|---------------|
| Product type description | TKM/9024VDC |
| Article number (order number) | 101010229 |
| EAN (European Article Number) | 4030661459097 |
| eCl@ss number, version 12.0 | 27-27-26-03 |
| eCl@ss number, version 11.0 | 27-27-26-03 |
| eCl@ss number, version 9.0 | 27-27-26-03 |
| ETIM number, version 7.0 | EC002593 |
| ETIM number, version 6.0 | EC002593 |

Approvals - Standards

| | |
|--------------|---------------------|
| Certificates | cULus CCC EAC |
|--------------|---------------------|

General data

| | |
|--|------------------------------------|
| Standards | EN ISO 13849-1 EN IEC 60947-5-1 |
| Coding level according to EN ISO 14119 | Low |
| Working principle | electromechanical |
| Enclosure material | Aluminium |

| | |
|--------------------------------------|---------|
| Material of the contacts, electrical | Silver |
| Gross weight | 1,400 g |

General data - Features

| | |
|--------------------------------|-----|
| Power to lock | Yes |
| Number of actuating directions | 3 |
| Number of auxiliary contacts | 2 |
| Number of safety contacts | 2 |

Safety classification

| | |
|--------------|----------------|
| Standards | EN ISO 13849-1 |
| Mission time | 20 Year(s) |

Safety classification - Safety outputs

| | |
|---|----------------------|
| B _{10D} Normally-closed contact (NC) | 2,000,000 Operations |
| B _{10D} Normally open contact (NO) | 1,000,000 Operations |

Mechanical data

| | |
|---|----------------------|
| Mechanical life, minimum | 2,000,000 Operations |
| Holding force F _{Zh} in accordance with EN ISO 14119 | 4,000 N |
| Latching force | 20 N |
| Positive break force, minimum | 20 N |
| Actuating speed, maximum | 0.3 m/s |

Mechanical data - Connection technique

| | |
|------------------------|---|
| Termination | Screw terminals |
| Cable section, minimum | 2 x 0.75 mm ² |
| Cable section, maximum | 2 x 2.5 mm ² |
| Note (Cable section) | All indications including the conductor ferrules. |

Mechanical data - Dimensions

| | |
|------------------|--------|
| Length of sensor | 50 mm |
| Width of sensor | 87 mm |
| Height of sensor | 192 mm |

Ambient conditions

| | |
|------------------------------|--------|
| Degree of protection | IP67 |
| Ambient temperature, minimum | +0 °C |
| Ambient temperature, maximum | +50 °C |

Ambient conditions - Insulation values

| | |
|---|--------|
| Rated insulation voltage U_i | 400 V |
| Rated impulse withstand voltage U_{imp} | 2.5 kV |

Electrical data

| | |
|---------------------------------------|------------------------|
| Thermal test current | 10 A |
| Rated control voltage | 24 VAC/DC |
| Electrical power consumption, maximum | 10 W |
| Switching element | NO contact, NC contact |
| Switching principle | Slow action |

Electrical data - Safety contacts

| | |
|-------------------------------------|---------|
| Voltage, Utilisation category AC-15 | 230 VAC |
| Current, Utilisation category AC-15 | 8 A |
| Voltage, Utilisation category DC-13 | 24 VDC |
| Current, Utilisation category DC-13 | 5 A |

Electrical data - Auxiliary contacts

| | |
|-------------------------------------|---------|
| Voltage, Utilisation category AC-15 | 230 VAC |
| Current, Utilisation category AC-15 | 8 A |
| Voltage, Utilisation category DC-13 | 24 VDC |
| Current, Utilisation category DC-13 | 5 A |

Scope of delivery

Scope of delivery Actuators must be ordered separately.

Pictures

Product picture (catalogue individual photo)



ID: ktkm-f04

| 280.8 kB | .jpg | 352.778 x 234.95 mm - 1000 x 666 px - 72 dpi

| 26.3 kB | .png | 74.083 x 49.389 mm - 210 x 140 px - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 22/01/2023, 21:58